



VG 2950

Principal dimension	Length p.p.	84.65 m	Performance	Installed power	kW
	Length o.a.	90 m		Main engine	kW
	Breadth moulded	13.75 m		Auxiliary/Emergency power	kW
	Depth moulded	5.55 m		Service speed (85% MCR)	kn
	Draught design	4.35 m		Trial speed	13.5 kn
	Air draught (max)	m		Endurance	days
Tonnage	Gross tonnage	2190	Cargo hold(s)	Cargo hold capacity	4261.2 m ³
	Net tonnage	1170		Hold dimensions abt.	61.9x10.6x6.45 m
	Deadweight	2900 t		Tanktop loading	12 t/m ²
Tanks capacity	Fresh water	75.3 m ³	Container capacity (TEU)	Reefers	-
	Heavy fuel oil	214 m ³		In hold	68 -
	Gas oil	66.8 m ³		On hatches	56 -
	Lube oil	6 m ³		Total capacity	124 -
	Dirty oil	4.6 m ³		Total capacity of 14t TEU	113 -
	Water ballast	1350 m ³			
Crane(s)	No. crane(s)	0 -	Container capacity (mix)	20 ft	13 -
	Max. lift capacity	0 t		40 ft	62 -
				45 ft	-



